



CorePro LEDtube EM/ Mains T8



CorePro LEDtube 1200mm 15.5W 830 T8

The CorePro LEDtube is an affordable LED solution suitable for replacing T8 fluorescent lamps. The product provides a natural lighting effect for use in general lighting applications, as well as instant energy savings – an environmentally friendly solution.

Warnings and Safety

• -

Product data

General Information	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Nominal lifetime	50,000 hour(s)
Switching Cycle	200,000
Lighting Technology	LED
Flux measurement reference	Sphere

Light Technical	
Color Code	830 [CCT of 3000K]
Beam Angle (Nom)	240 degree(s)
Luminous Flux	1,700 lm
Color Designation	White (WH)
Luminous Efficacy (rated) (Nom)	109 lm/W
Correlated Color Temperature (Nom)	3000 K
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %

Flickering value (PstLM) - Flickering value as per EN 61000-3-3	1
Stroboscopic effect visibility measure (SVM)	0.9
Photobiological safety according to EN 62471	RG0


Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	15.5 W
Lamp Current (Nom)	84 mA
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.9
Voltage (Nom)	220-240 V
LED alternative to fluorescent lamp power	36 W
Ballast Compatibility	EM/Mains

CorePro LEDtube EM/Mains T8

Temperature	
Ambient temperature range	-20 °C to 45 °C
T-Case Maximum (Nom)	60 °C
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Frosted
Bulb Material	Glass
Product Length	1,200 mm
Bulb Shape	T8
Approval and Application	
Energy Efficiency Class	F
Energy Saving Product	Yes
Approval Marks	RoHS compliance CE marking KEMA Keur certificate



Energy Consumption kWh/1000 h	16 kWh
EPREL Registration Number	1827706
EU RoHS compliant	Yes
Product Data	
Order product name	CorePro LEDtube 1200mm 15.5W 830 T8
Full product name	CorePro LEDtube 1200mm 15.5W 830 T8
Full product code	871951448640900
Order code	48640900
Material Nr. (12NC)	929003577232
Net Weight (Piece)	0.220 kg
EAN/UPC - Product/Case	8719514486409
Numerator - Packs per outer box	20
EAN/UPC - Case	8719514486416

Dimensional drawing



Product	D1	D2	A1	A2	A3
CorePro LEDtube 1200mm 15.5W 830 T8	25.7 mm	28 mm	1,198 mm	1,205 mm	1,212 mm

Photometric data




Spectral Power Distribution Colour - CorePro LEDtube 1200mm 15.5W 830 T8

Light Distribution Diagram - CorePro LEDtube 1200mm 15.5W 830 T8



CorePro LEDtube EM/Mains T8

Photometric data





General uniform lighting - CorePro LEDtube 1200mm 15.5W 830 T8

Lifetime



Lumen Maintenance Diagram - CorePro LEDtube 1200mm 15.5W 830 T8

Life Expectancy Diagram




LifetimeVsTc

FailureRate

CorePro LEDtube EM/Mains T8

Lifetime



Lumen Maintenance Diagram - CorePro LEDtube 1200mm 15.5W 830 T8

