



CorePro Plastic LEDcandles & lusters



CorePro lustre ND 5-40W E14 865 P45 FR

The frosted CorePro LEDcandle is designed for retrofit replacement of incandescent lamps. It is compatible with fixtures with an E14 holder and is an attractive product for chandeliers. LEDlamps deliver huge energy savings and minimize maintenance cost.

Product data

General Information	
Cap-Base	E14
Nominal lifetime	15,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere
Light Technical	
Color Code	865 [CCT of 6500K]
Luminous Flux	470 lm
Color Designation	Cool Daylight
Luminous Efficacy (rated) (Nom)	94.00 lm/W
Correlated Color Temperature (Nom)	6500 K
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Flickering value (PstLM) - Flickering value as pe	er 1
EN 61000-3-3	
Stroboscopic effect visibility measure (SVM)	0.4
Photobiological safety according to EN 62471	RG1

Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	5 W
Lamp Current (Nom)	44 mA
Wattage Equivalent	40 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.51
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	81 °C
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Frosted


Datasheet, 2023, August 28 data subject to change

CorePro Plastic LEDcandles & lusters

Bulb Shape	P45
Approval and Application	
Energy Efficiency Class	F
Energy Consumption kWh/1000 h	5 kWh
EPREL Registration Number	453205
CE mark	Yes
EU RoHS compliant	Yes
EyeComfort	Yes
Application Conditions	
can it be used in closed luminaires	No
Product Data	
Order product name	CorePro lustre ND 5-40W E14 865 P45
	FR


Full product name	CorePro lustre ND 5-40W E14 865 P45
	FR
Full product code	871951431272200
Order code	31272200
Material Nr. (12NC)	929002970402
Net Weight (Piece)	0.020 kg
EAN/UPC - Product/Case	8719514312722
Numerator - Packs per outer box	10
EAN/UPC - Case	8719514312739


Dimensional drawing




Product	D	С
CorePro lustre ND 5-40W E14 865 P45 FR	45 mm	88 mm

Photometric data








General uniform lighting - CorePro lustre ND 5-40W E14 865 P45 FR


CorePro Plastic LEDcandles & lusters


Photometric data



Spectral Power Distribution Colour - CorePro lustre ND 5-40W E14 865 P45 FR

Lifetime





Life Expectancy Diagram

Lumen Maintenance Diagram - CorePro lustre ND 5-40W E14 865 P45 FR



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.