



E A C

CorePro Plastic LEDcandles & lusters

CorePro lustre ND 7-60W E27 840 P48 FR

The frosted CorePro LEDcandle is designed for retrofit replacement of incandescent lamps. It is compatible with fixtures with an E14 holder and is an attractive product for chandeliers. LEDlamps deliver huge energy savings and minimize maintenance cost.

Product data

General Information	
	507
Cap-Base	E27
Nominal lifetime	15,000 hour(s)
Switching Cycle	50,000
Lighting Technology	LED
Flux measurement reference	Sphere
Light Technical	
Color Code	840 [CCT of 4000K]
Luminous Flux	806 lm
Color Designation	Cool White (CW)
Luminous Efficacy (rated) (Nom)	115.00 lm/W
Correlated Color Temperature (Nom)	4000 K
Color Consistency	<6
Color rendering index (CRI)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Flickering value (PstLM) - Flickering value as	1
per EN 61000-3-3	
Stroboscopic effect visibility measure (SVM)	0.4
Photobiological safety according to EN 62471	RG1

Operating and Electrical	
Line Frequency	50 to 60 Hz
Input Frequency	50 to 60 Hz
Power Consumption	7 W
Lamp Current (Nom)	59 mA
Wattage Equivalent	60 W
Starting Time (Nom)	0.5 s
Warm-up time to 60% light	0.5 s
Power Factor (Fraction)	0.51
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	83 °C
Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Bulb Finish	Frosted

Datasheet, 2023, August 28 data subject to change

CorePro Plastic LEDcandles & lusters

Bulb Shape	P48
Approval and Application	
Energy Efficiency Class	E
Energy Consumption kWh/1000 h	7 kWh
EPREL Registration Number	453215
CE mark	Yes
EU RoHS compliant	Yes
EyeComfort	Yes
Application Conditions	
can it be used in closed luminaires	No
Product Data	
Order product name	CorePro lustre ND 7-60W E27 840 P48
	FR


Full product name	CorePro lustre ND 7-60W E27 840 P48	
	FR	
Full product code	871951431306400	
Order code	31306400	
Material Nr. (12NC)	929002973202	
Net Weight (Piece)	0.028 kg	
EAN/UPC - Product/Case	8719514313064	
Numerator - Packs per outer box	10	
EAN/UPC - Case	8719514313071	

Dimensional drawing




Product	D	С
CorePro lustre ND 7-60W E27 840 P48 FR	48 mm	95 mm

Photometric data








Spectral Power Distribution Colour - CorePro lustre ND 7-60W E27 840 P48 FR


CorePro Plastic LEDcandles & lusters


Photometric data



Light Distribution Diagram - CorePro lustre ND 7-60W E27 840 P48 FR

Lifetime





Life Expectancy Diagram

Lumen Maintenance Diagram - CorePro lustre ND 7-60W E27 840 P48 FR



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.